PYRO-SAFE Firestop pipe sleeve



Product description

Fields of application

Pipe sealing for combustible pipes (PVC, PP, PE-HD, ASA, ABS und PE-X).

For application onto solid walls, floors as well as plasterboard walls. In case of fire, the high performance intumescent material will expand and seal structural openings with a rigid foam. The spread of fire and smoke through the opening is prevented.

Product features

Detachable steel-sheet enclosures available in different sizes, with internal layers of highly efficient intumescent material; very small dimensions; only a few fastening points; no loose parts; quick installation with no drilling templates; installation even in difficult situations; also ideal for renovation and Retrospective installation; easy to seal e.g. with mortar (mounting brackets only).

Fire rating of system

Up to 4 hours

Applicability certificate

Tested and approved according to national and international standards as e.g.: DIN, BS EN, other standards on request

Pipes



Technical Data

Handling

- Larger sleeves are allowed to be used in difficult situations (up to three sizes larger)
- Zero distance for pipes lying next to each other
- For more information see the installation instructions

Ordering information

1 piece without fixing equipment

Storage

Cool and dry

Consumption

For wall penetrations: 2 sleevesFor floor penetrations: 1 sleeve

Safety instructions

Please refer to our MSDS (safety data sheet).

Technical data

size + max. pipe-Ø in mm	Interior-Ø in mm	Exterior-Ø in mm	Construction height in mm	Brackets
32	36	50	26	2
40	44	58	26	2
50	54	68	26	2
63	67	94	26	4
75	79	106	26	4
90	94	132	26.6	4
110	114	155	26.6	4
125	129	172	40	4
140	144	200	40	6
160	164	220	40	6

Applied systems

• PYRO-SAFE Firestop pipe sleeve

